

L

A

M

P

I

R

A

N

Lampiran 1 – Listing program

text/x-generic Bussiness.php (C++ source, ASCII text)
<?php

```
namespace App\Models;

use
    Illuminate\Database\Eloquent\Factories\Has
    Factory;
use Illuminate\Database\Eloquent\Model;

class Bussiness extends Model
{
    use HasFactory;

    protected $fillable = [
        'id_satuan',
        'id_kbli',
        'nama_pemilik',
        'jenis_kelamin',
        'nama_usaha',
        'alamat_pemilik',
        'no_hp_pemilik',
        'kecamatan',
        'kelurahan',
        'tahun_izin',
        'tenaga_laki',
        'tenaga_perempuan',
        'kapasitas_produksi',
        'nilai_investasi',
        'nilai_produksi',
        'bentuk_badan_usaha',
        'nama_produk',
        'lat',
        'lng',
        'lokasi',
        'bahan_baku'
    ];

    public function unit() {
        return $this->belongsTo(Unit::class, 'id_satuan',
            'id');
    }

    public function kbli() {
        return $this->belongsTo(Kbli::class, 'id_kbli', 'id');
    }
}
```

text/x-generic FieldCode.php (C++ source, ASCII text)
<?php

```
namespace App\Models;

use
    Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class FieldCode extends Model
{
    use HasFactory;
}
```

text/x-generic Kbli.php (C++ source, ASCII text)
<?php

```
namespace App\Models;

use
    Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
```

```
class Kbli extends Model
{
    use HasFactory;
```

```
    protected $table = 'kbli';

    protected $fillable = [
        'kode',
        'name'
    ];
}
```

text/x-generic Unit.php (C++ source, ASCII text)
<?php

```
namespace App\Models;
use
    Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class Unit extends Model
{
    use HasFactory;

    protected $fillable = [
        'name',
    ];
}
```

text/x-generic User.php (C++ source, ASCII text)
<?php

```
namespace App\Models;

use Illuminate\Contracts\Auth\MustVerifyEmail;
use
    Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as
    Authenticatable;
use Illuminate\Notifications\Notifiable;
use Laravel\Sanctum\HasApiTokens;
class User extends Authenticatable
{
    use HasApiTokens, HasFactory, Notifiable;

    /**
     * The attributes that are mass assignable.
     *
     * @var array<int, string>
     */
    protected $fillable = [
        'name',
        'email',
        'password',
    ];

    /**
     * The attributes that should be hidden for
    serialization.
     *
     * @var array<int, string>
     */
    protected $hidden = [
        'password',
        'remember_token',
    ];

    /**
     * The attributes that should be cast.
```

```

*
* @var array<string, string>
*/
protected $casts = [
    'email_verified_at' => 'datetime',
];
}

text/x-generic Kernel.php ( C++ source, ASCII text )
<?php

namespace App\Http;

use Illuminate\Foundation\Http\Kernel as HttpKernel;

class Kernel extends HttpKernel
{
    /**
     * The application's global HTTP middleware stack.
     *
     * These middleware are run during every request to
     * your application.
     *
     * @var array<int, class-string|string>
     */
    protected $middleware = [
        // \App\Http\Middleware\TrustHosts::class,
        \App\Http\Middleware\TrustProxies::class,
        \Fruitcake\Cors\HandleCors::class,

        \App\Http\Middleware\PreventRequestsDuringMaintenance::class,

        \Illuminate\Foundation\Http\Middleware\ValidatePostSize::class,
        \App\Http\Middleware\TrimStrings::class,

        \Illuminate\Foundation\Http\Middleware\ConvertEmptyStringsToNull::class,
    ];

    /**
     * The application's route middleware groups.
     *
     * @var array<string, array<int, class-string|string>>
     */
    protected $middlewareGroups = [
        'web' => [
            \App\Http\Middleware\EncryptCookies::class,

            \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::class,

            \Illuminate\Session\Middleware\StartSession::class,
            //
            \Illuminate\Session\Middleware\AuthenticateSession::class,

            \Illuminate\View\Middleware\ShareErrorsFromSession::class,
            \App\Http\Middleware\VerifyCsrfToken::class,

            \Illuminate\Routing\Middleware\SubstituteBindings::class,
        ],

        'api' => [

```

```

//
\Laravel\Sanctum\Http\Middleware\EnsureFrontendRequestsAreStateful::class,
    'throttle:api',

    \Illuminate\Routing\Middleware\SubstituteBindings::class,
],
];

/**
 * The application's route middleware.
 *
 * These middleware may be assigned to groups or
 * used individually.
 *
 * @var array<string, class-string|string>
 */
protected $routeMiddleware = [
    'auth' =>
        \App\Http\Middleware\Authenticate::class,
    'auth.basic' =>
        \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
    'cache.headers' =>
        \Illuminate\Http\Middleware\SetCacheHeaders::class,
    'can' =>
        \Illuminate\Auth\Middleware\Authorize::class,
    'guest' =>
        \App\Http\Middleware\RedirectIfAuthenticated::class,
    'password.confirm' =>
        \Illuminate\Auth\Middleware\RequirePassword::class,
    'signed' =>
        \Illuminate\Routing\Middleware\ValidateSignature::class,
    'throttle' =>
        \Illuminate\Routing\Middleware\ThrottleRequests::class,
    'verified' =>
        \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
];
}

text/x-generic dashboard.blade.php ( ASCII text )
<x-app-layout>
    <x-slot name="header">
        <h2 class="font-semibold text-xl text-gray-800 leading-tight">
            {{ __('Dashboard') }}
        </h2>
    </x-slot>

    <div class="py-12">
        <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
            <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
                <div class="p-6 text-gray-900">
                    {{ __('You're logged in!') }}
                </div>
            </div>
        </div>
    </x-app-layout>

text/x-generic home.blade.php ( HTML document, ASCII text )
<!DOCTYPE html>

```

```

<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-
width, initial-scale=1.0">
  <meta http-equiv="X-UA-Compatible"
content="ie=edge">
  <title>Home - Pelaporan UMKM</title>

  <!-- Scripts -->
  @vite(['resources/css/app.css', 'resources/js/app.js'])
</head>

<body style="background-image:
url('../images/background.jpg')">
  <div class="relative overflow-hidden bg-gray-50">
    <div class="hidden sm:block sm:absolute
sm:inset-y-0 sm:h-full sm:w-full" aria-hidden="true">
      <div class="relative h-full mx-auto max-w-
7xl">
        <svg class="absolute transform right-full
translate-y-1/4 translate-x-1/4 lg:translate-x-1/2"
width="404" height="784" fill="none"
viewBox="0 0 404 784">
          <defs>
            <pattern id="f210dbf6-a58d-4871-961e-
36d5016a0f49" x="0" y="0" width="20" height="20"
patternUnits="userSpaceOnUse">
              <rect x="0" y="0" width="4"
height="4" class="text-gray-200" fill="currentColor" />
            </pattern>
          </defs>
          <rect width="404" height="784"
fill="url(#f210dbf6-a58d-4871-961e-36d5016a0f49)"
/ >
        </svg>
        <svg class="absolute transform left-full -
translate-y-3/4 -translate-x-1/4 md:-translate-y-1/2 lg:-
translate-x-1/2"
width="404" height="784" fill="none"
viewBox="0 0 404 784">
          <defs>
            <pattern id="5d0dd344-b041-4d26-
bec4-8d33ea57ec9b" x="0" y="0" width="20"
height="20"
patternUnits="userSpaceOnUse">
              <rect x="0" y="0" width="4"
height="4" class="text-gray-200" fill="currentColor" />
            </pattern>
          </defs>
          <rect width="404" height="784"
fill="url(#5d0dd344-b041-4d26-bec4-8d33ea57ec9b)"
/ >
        </svg>
      </div>
    </div>
  </div>

  <div x-data="{show: false}" class="relative pt-6
pb-16 sm:pb-24">
    <div>
      <div class="px-4 mx-auto max-w-7xl sm:px-
6">
        <nav class="relative flex items-center
justify-between sm:h-10 md:justify-center"
aria-label="Global">
          <div class="flex items-center flex-1
md:absolute md:inset-y-0 md:left-0">

```

```

          <div class="flex items-center justify-
between w-full md:w-auto">
            <a href="#">
              <span class="sr-
only">Workflow</span>
              
            </a>
          <div class="flex items-center -mr-2
md:hidden">
            <button type="button"
@click="show = true"
class="inline-flex items-center
justify-center p-2 text-gray-400 rounded-md bg-gray-50
hover:text-gray-500 hover:bg-gray-100 focus:outline-
none focus:ring-2 focus:ring-inset focus:ring-indigo-
500"
aria-expanded="false">
              <span class="sr-only">Open
main menu</span>
            <!-- Heroicon name:
outline/menu -->
            <svg class="w-6 h-6"
xmlns="http://www.w3.org/2000/svg" fill="none"
viewBox="0 0 24 24"
stroke="currentColor" aria-hidden="true">
              <path stroke-
linecap="round" stroke-linejoin="round" stroke-
width="2"
d="M4 6h16M4
12h16M4 18h16" />
            </svg>
          </button>
        </div>
      </div>
    </div>
    <div class="hidden md:absolute md:flex
md:items-center md:justify-end md:inset-y-0 md:right-
0">
      <span class="inline-flex rounded-md
shadow">
        <a href="{{ route('login') }}"
class="inline-flex items-center
px-4 py-2 text-base font-medium text-indigo-600 bg-
white border border-transparent rounded-md hover:bg-
gray-50">
          Log in </a>
        </span>
      </div>
    </nav>
  </div>

  <!--
Mobile menu, show/hide based on menu open
state.

Entering: "duration-150 ease-out"
From: "opacity-0 scale-95"
To: "opacity-100 scale-100"
Leaving: "duration-100 ease-in"
From: "opacity-100 scale-100"
To: "opacity-0 scale-95"
-->
  <div x-show="show"
class="absolute inset-x-0 top-0 z-10 p-2
transition origin-top-right transform md:hidden">

```

```

        <div class="overflow-hidden bg-white
rounded-lg shadow-md ring-1 ring-black ring-opacity-
5">
        <div class="flex items-center justify-
between px-5 pt-4">
            <div>
                
            </div>
            <div class="-mr-2">
                <button type="button"
@click="show = false"
class="inline-flex items-center
justify-center p-2 text-gray-400 bg-white rounded-md
hover:text-gray-500 hover:bg-gray-100 focus:outline-
none focus:ring-2 focus:ring-inset focus:ring-indigo-
500">
                    <span class="sr-only">Close
menu</span>
                    <!-- Heroicon name: outline/x -->
                    <svg class="w-6 h-6"
xmlns="http://www.w3.org/2000/svg" fill="none"
viewBox="0 0 24 24"
stroke="currentColor" aria-hidden="true">
                        <path stroke-linecap="round"
stroke-linejoin="round" stroke-width="2"
d="M6 18L18 6M6 6L12 12"
/>
                    </svg>
                </button>
            </div>
        </div>
        <a href="{{ route('login') }}"
class="block w-full px-5 py-3 font-
medium text-center text-indigo-600 bg-gray-50
hover:bg-gray-100">
            Log in </a>
        </div>
    </div>
</div>

<main class="px-4 mx-auto mt-16 max-w-7xl
sm:mt-24">
    <div class="text-center">
        <h1 class="text-4xl font-extrabold
tracking-tight text-gray-900 mb-28 sm:text-5xl md:text-
6xl">
            <span class="block xl:inline">Halaman
pelaporan</span>
            <span class="block text-indigo-600
xl:inline">UMKM</span>
        </h1>
        {{ -- <div class="max-w-md mx-auto mt-5
sm:flex sm:justify-center md:mt-8">
            <div class="rounded-md shadow">
                <a href="{{ route('lapor.index') }}"
class="flex items-center justify-
center w-full px-8 py-3 text-base font-medium text-
white bg-indigo-600 border border-transparent rounded-
md hover:bg-indigo-700 md:py-4 md:text-lg md:px-
10">
                    Lapor Sekarang </a>
                </div>
            </div> --}}
        </div>
    </div>
</main>

```

```

</div>

<div class="py-12">
    <div class="mx-auto max-w-7xl sm:px-6 lg:px-
8">
        <div class="flex flex-col">
            <div class="-my-2 overflow-x-auto sm:-mx-6
lg:-mx-8">
                <div class="inline-block min-w-full py-2
align-middle sm:px-6 lg:px-8">
                    <div class="overflow-hidden border-b
border-gray-200 shadow sm:rounded-lg">
                        <table class="min-w-full divide-y
divide-gray-200">
                            <thead class="bg-gray-50">
                                <tr>
                                    <th scope="col"
class="px-6 py-3 text-xs
font-medium tracking-wider text-left text-gray-500
uppercase">
                                        Nama Pemilik</th>
                                    <th scope="col"
class="px-6 py-3 text-xs
font-medium tracking-wider text-left text-gray-500
uppercase">
                                        Nama Usaha</th>
                                    <th scope="col"
class="px-6 py-3 text-xs
font-medium tracking-wider text-left text-gray-500
uppercase">
                                        Alamat Pemilik</th>
                                    <th scope="col"
class="px-6 py-3 text-xs
font-medium tracking-wider text-left text-gray-500
uppercase">
                                        No HP</th>
                                <tr>
                                    <th scope="col"
class="relative px-6 py-3">
                                        <span class="sr-
only">Edit</span>
                                    </th>
                                </tr>
                            </thead>
                            <tbody>
                                @foreach ($businesses as
$business)
                                    <tr class="odd:bg-white even:bg-
gray-50">
                                        <td class="px-6 py-4 text-sm
font-medium text-gray-900 whitespace-nowrap">{{
$business->nama_pemilik
}}
                                        </td>
                                        <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
$business->nama_usaha
}}</td>
                                        <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
$business->alamat_pemilik
}}</td>
                                        <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
$business->no_hp_pemilik
}}</td>
                                        <td
class="flex px-6 py-4 space-
x-1 text-sm font-medium text-right max-w-1
whitespace-nowrap">

```

```

<a href="{{
route('industri.edit', $bussiness) }}"
class="text-indigo-600
hover:text-indigo-900">Edit</a>
<form method="POST"
action="{{ route('industri.destroy', $bussiness) }}">
    @csrf
    @method('DELETE')
    <button type="submit"
class="text-red-600
hover:text-red-900">Delete</button>
</form>
</td>
</tr>
<@endforeach
</tbody>
</table>
</div>
</div>
</div>
</div>
</div>
</div>
</body>
</html>

text/x-generic create.blade.php ( HTML document,
ASCII text, with very long lines )
<x-app-layout>
    <x-slot name="header">
        <h2 class="text-xl font-semibold leading-tight
text-gray-800">
            Industri
        </h2>
    </x-slot>

    <style>
        gmp-map {
            height: 100%;
        }
    </style>

    <div class="py-12">
        <div class="mx-auto max-w-7xl sm:px-6 lg:px-
8">
            <div class="flex flex-col">
                <div class="-my-2 overflow-x-auto sm:-mx-6
lg:-mx-8">
                    <div class="inline-block min-w-full py-2
align-middle sm:px-6 lg:px-8">
                        <div class="overflow-hidden border-b
border-gray-200 bg-white p-8 shadow sm:rounded-lg">
                            <form class="space-y-8 divide-y
divide-gray-200" x-data="form_data" method="POST"
action="{{ route('industri.store')
}}">
                                <div class="mt-6 grid grid-cols-1
gap-x-4 gap-y-6 sm:grid-cols-2">
                                    @csrf
                                    <div class="sm:col-span-3">
                                        <label class="block text-sm
font-medium text-gray-700" for="nama_pemilik">
                                            Nama
                                            Pemilik </label>
                                        <div class="mt-1">
                                            <input

```

```

class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="nama_pemilik"
name="nama_pemilik" type="text"
value="{{
old('nama_pemilik') }}"
autocomplete="nama_pemilik">
</div>
@error('nama_pemilik')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
    <label class="block text-sm
font-medium text-gray-700" for="jenis_kelamin">
        Jenis Kelamin </label>
    <div class="mt-1">
        <select
            class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
            name="jenis_kelamin"
            id="jenis_kelamin">
                <option {{
old('jenis_kelamin')=='Laki-laki' ? 'selected' : '' }}
                    value="Laki-
laki">Laki-laki</option>
                <option {{
old('jenis_kelamin')=='Perempuan' ? 'selected' : '' }}
                    value="Perempuan">Perempuan</option>
            </select>
        </div>
        @error('jenis_kelamin')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-3">
        <label class="block text-sm
font-medium text-gray-700" for="nama_usaha"> Nama
            Usaha </label>
        <div class="mt-1">
            <input
                class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                id="nama_usaha"
                name="nama_usaha" type="text"
                value="{{
old('nama_usaha') }}" autocomplete="nama_usaha">
            </div>
            @error('nama_usaha')
            <span class="text-xs text-red-
400">{{ $message }}</span>
            @enderror
        </div>
        <div class="sm:col-span-3">
            <label class="block text-sm
font-medium text-gray-700" for="alamat_pemilik">
                Alamat Pemilik </label>
            <div class="mt-1">
                <input
                    class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"

```

```

        id="alamat_pemilik"
name="alamat_pemilik" type="text"
        value="{{
old('alamat_pemilik') }}"
autocomplete="alamat_pemilik">
</div>
        @error('alamat_pemilik')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="no_hp_pemilik"> No
HP </label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="no_hp_pemilik"
name="no_hp_pemilik" type="text"
value="{{
old('no_hp_pemilik') }}"
autocomplete="no_hp_pemilik">
</div>
        @error('no_hp_pemilik')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="id_kecamatan">
Kecamatan </label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="kecamatan"
name="kecamatan" type="text"
value="{{
old('kecamatan') }}" autocomplete="kecamatan">
</div>
        @error('id_kecamatan')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="id_kelurahan">
Kelurahan </label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="kelurahan"
name="kelurahan" type="text"
value="{{
old('kelurahan') }}" autocomplete="kelurahan">
</div>
        @error('id_kelurahan')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>

```

```

<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="id_kbli">
Bentuk Usaha </label>
<div class="mt-1">
<select
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="id_kbli"
name="id_kbli" autocomplete="id_kbli"
@change="kbliChange"
x-model="selectedId">
<template x-for="kbli in
list_kbli" :key="kbli.id">
<option
:value="kbli.id" x-text="kbli.name">
</option>
</template>
</select>
</div>
        @error('id_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="tahun_izin"> Tahun
Izin </label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="tahun_izin"
name="tahun_izin" type="text"
value="{{
old('tahun_izin') }}" autocomplete="tahun_izin">
</div>
        @error('tahun_izin')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="no_kbli"> No KBLI
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 bg-gray-200 shadow-sm
focus:border-indigo-500 focus:ring-indigo-500 sm:text-
sm"
id="no_kbli"
name="no_kbli" type="text" readonly
autocomplete="no_kbli"
:value="getSelectedText()">
</div>
        @error('no_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="tenaga_laki"> Tenaga

```

```

        Kerja Laki-laki
    </label>
    <div class="mt-1">
        <input
            class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
            id="tenaga_laki"
            name="tenaga_laki" type="text"
            value="{{
old('tenaga_laki') }}" autocomplete="tenaga_laki">
        </div>
        @error('tenaga_laki')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-3">
        <label class="block text-sm
font-medium text-gray-700" for="tenaga_perempuan">
            Tenaga Kerja
            Perempuan
        </label>
        <div class="mt-1">
            <input
                class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                id="tenaga_perempuan"
                name="tenaga_perempuan" type="text"
                value="{{
old('tenaga_perempuan') }}"
                autocomplete="tenaga_perempuan">
            </div>
            @error('tenaga_perempuan')
            <span class="text-xs text-red-
400">{{ $message }}</span>
            @enderror
        </div>
        <div class="sm:col-span-3">
            <label class="block text-sm
font-medium text-gray-700" for="kapasitas_produksi">
                Kapasitas Produksi Perhari
            </label>
            <div class="mt-1">
                <input
                    class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                    id="kapasitas_produksi"
                    name="kapasitas_produksi" type="text"
                    value="{{
old('kapasitas_produksi') }}"
                    autocomplete="kapasitas_produksi">
                </div>
                @error('kapasitas_produksi')
                <span class="text-xs text-red-
400">{{ $message }}</span>
                @enderror
            </div>
            <div class="sm:col-span-3">
                <label class="block text-sm
font-medium text-gray-700" for="satuan"> Satuan
            </label>
            <div class="mt-1">
                <select

```

```

            class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
            id="id_satuan"
            name="id_satuan">
                @foreach ($units as
$unit)
                    <option value="{{ $unit-
>id }}" {{ old('id_satuan')==$unit->id ?
'selected' : " " }}>
                        {{ $unit->name }}
                    </option>
                @endforeach
            </select>
        </div>
        @error('id_satuan')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-3">
        <label class="block text-sm
font-medium text-gray-700" for="nilai_investasi">
            Nilai Investasi
        </label>
        <div class="mt-1">
            <div class="flex rounded-
md shadow-sm">
                <span
                    class="inline-flex
items-center px-3 rounded-l-md border border-r-0
border-gray-300 bg-gray-50 text-gray-500 sm:text-
sm">
                    Rp
                </span>
                <input type="text"
                    id="nilai_investasi" name="nilai_investasi"
                    autocomplete="nilai_investasi" value="{{
old('nilai_investasi') }}"
                    class="flex-1 block w-
full focus:ring-indigo-500 focus:border-indigo-500
min-w-0 rounded-none rounded-r-md sm:text-sm
border-gray-300">
            </div>
            </div>
            @error('nilai_investasi')
            <span class="text-xs text-red-
400">{{ $message }}</span>
            @enderror
        </div>
        <div class="sm:col-span-3">
            <label class="block text-sm
font-medium text-gray-700" for="nilai_produksi">
                Nilai Produksi
            </label>
            <div class="mt-1">
                <div class="flex rounded-
md shadow-sm">
                    <span
                        class="inline-flex
items-center px-3 rounded-l-md border border-r-0
border-gray-300 bg-gray-50 text-gray-500 sm:text-
sm">
                        Rp
                    </span>
                    <input type="text"
                        id="nilai_produksi" name="nilai_produksi"

```



```

autocomplete="nilai_produksi" value="{{
old('nilai_produksi') }}"
class="flex-1 block w-
full focus:ring-indigo-500 focus:border-indigo-500
min-w-0 rounded-none rounded-r-md sm:text-sm
border-gray-300">
</div>
</div>
<div>
<@error('nilai_produksi')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700"
for="bentuk_badan_usaha">
    Bentuk Badan Usaha
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="bentuk_badan_usaha"
name="bentuk_badan_usaha" type="text"
value="{{
old('bentuk_badan_usaha') }}"
autocomplete="bentuk_badan_usaha">
</div>
<@error('bentuk_badan_usaha')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="nama_produk">
    Nama Produk
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="nama_produk"
name="nama_produk" type="text"
value="{{
old('nama_produk') }}" autocomplete="nama_produk">
</div>
<@error('nama_produk')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="bahan_baku">
    Bahan Baku
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="bahan_baku"
name="bahan_baku" type="text"

```

```

value="{{
old('bahan_baku') }}" autocomplete="bahan_baku">
</div>
<@error('bahan_baku')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-6">
<h4 class="text-lg font-
medium text-gray-800">Data Lokasi</h4>
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="nilai_produksi">
    Titik Latitude
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="lat" name="lat"
type="text" value="{{ old('lat') }}" readonly>
</div>
<@error('lat')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-3">
<label class="block text-sm
font-medium text-gray-700" for="nilai_produksi">
    Titik Longitude
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="lng" name="lng"
type="text" value="{{ old('lng') }}" readonly>
</div>
<@error('lng')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>
<div class="sm:col-span-6">
<label class="block text-sm
font-medium text-gray-700" for="lokasi">
    Lokasi
</label>
<div class="mt-1">
<input
class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
id="lokasi"
name="lokasi" type="text" value="{{ old('lokasi') }}"
autocomplete="lokasi"
readonly>
</div>
<@error('lokasi')
<span class="text-xs text-red-
400">{{ $message }}</span>
</div>
</div>

```



```

<input type="text"
name="no_hp_pemilik" id="no_hp_pemilik"

autocomplete="no_hp_pemilik"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('no_hp_pemilik', $business->no_hp_pemilik) }}">
</div>
@error('no_hp_pemilik')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="id_kecamatan">
class="block text-sm font-medium text-gray-700">
Kecamatan </label>
<div class="mt-1">
<input type="text"
name="kecamatan" id="kecamatan"
autocomplete="kecamatan"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('kecamatan', $business->kecamatan) }}">
</div>
@error('id_kecamatan')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="id_kelurahan">
class="block text-sm font-medium text-gray-700">
Kelurahan </label>
<div class="mt-1">
<input type="text"
name="kelurahan" id="kelurahan"
autocomplete="kelurahan"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{ old('kelurahan',
$business->kelurahan) }}">
</div>
@error('id_kelurahan')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="id_kbli">
class="block text-sm font-medium text-gray-700">
Bentuk Usaha </label>
<div class="mt-1">
<select name="id_kbli"
id="id_kbli" autocomplete="id_kbli"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
@change="kbliChange"
x-model="selectedId">
<template x-for="kbli in
list_kbli" :key="kbli.id">
<option
:value="kbli.id" x-text="kbli.name">

```

```

</option>
</template>
</select>
</div>
@error('id_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="tahun_izin">
class="block text-sm font-medium text-gray-700">
Tahun
Izin </label>
<div class="mt-1">
<input type="text"
name="tahun_izin" id="tahun_izin"
autocomplete="tahun_izin"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('tahun_izin', $business->tahun_izin) }}">
</div>
@error('tahun_izin')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="no_kbli">
class="block text-sm font-medium text-gray-700">
No
KBLI
</label>
<div class="mt-1">
<input type="text" readonly
name="no_kbli" id="no_kbli"
autocomplete="no_kbli"
class="block w-full bg-
gray-200 border-gray-300 rounded-md shadow-sm
focus:ring-indigo-500 focus:border-indigo-500 sm:text-
sm"
:value="getSelectedText()">
</div>
@error('no_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="tenaga_laki">
class="block text-sm font-medium text-gray-700">
Tenaga
Kerja Laki-laki
</label>
<div class="mt-1">
<input type="text"
name="tenaga_laki" id="tenaga_laki"
autocomplete="tenaga_laki"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('tenaga_laki', $business->tenaga_laki) }}">
</div>
@error('tenaga_laki')

```

```

<span class="text-xs text-red-400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label
for="tenaga_perempuan" class="block text-sm font-medium text-gray-700">
Tenaga Kerja Perempuan
</label>
<div class="mt-1">
<input type="text"
name="tenaga_perempuan" id="tenaga_perempuan"
autocomplete="tenaga_perempuan"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('tenaga_perempuan', $business->tenaga_perempuan) }}">
</div>
@error('tenaga_perempuan')
<span class="text-xs text-red-400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label
for="kapasitas_produksi" class="block text-sm font-medium text-gray-700">
Kapasitas Produksi Perhari
</label>
<div class="mt-1">
<input type="text"
name="kapasitas_produksi" id="kapasitas_produksi"
autocomplete="kapasitas_produksi"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('kapasitas_produksi', $business->kapasitas_produksi) }}">
</div>
@error('kapasitas_produksi')
<span class="text-xs text-red-400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="satuan"
class="block text-sm font-medium text-gray-700">
Satuan
</label>
<div class="mt-1">
<select name="id_satuan"
id="id_satuan"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm">
@foreach ($units as $unit)
<option value="{{ $unit->id }}" {{ old('id_satuan', $business->id_satuan) == $unit->id
?

```

```

'selected' : " " }}>{{
$unit->name }}
</option>
@endforeach
</select>
</div>
@error('id_satuan')
<span class="text-xs text-red-400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="nilai_investasi"
class="block text-sm font-medium text-gray-700">
Nilai Investasi
</label>
<div class="mt-1">
<div class="flex rounded-md shadow-sm">
<span
class="inline-flex items-center px-3 rounded-l-md border border-r-0 border-gray-300 bg-gray-50 text-gray-500 sm:text-sm">
Rp
</span>
<input type="text"
id="nilai_investasi" name="nilai_investasi"
autocomplete="nilai_investasi"
value="{{
round(old('nilai_investasi', $business->nilai_investasi))
}}"
class="flex-1 block w-full focus:ring-indigo-500 focus:border-indigo-500 min-w-0 rounded-none rounded-r-md sm:text-sm border-gray-300">
</div>
</div>
@error('nilai_investasi')
<span class="text-xs text-red-400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="nilai_produksi"
class="block text-sm font-medium text-gray-700">
Nilai Produksi
</label>
<div class="mt-1">
<div class="flex rounded-md shadow-sm">
<span
class="inline-flex items-center px-3 rounded-l-md border border-r-0 border-gray-300 bg-gray-50 text-gray-500 sm:text-sm">
Rp
</span>
<input type="text"
id="nilai_produksi" name="nilai_produksi"
autocomplete="nilai_produksi"
value="{{
round(old('nilai_produksi', $business->nilai_produksi))
}}"
class="flex-1 block w-full focus:ring-indigo-500 focus:border-indigo-500

```

```

min-w-0 rounded-none rounded-r-md sm:text-sm
border-gray-300">
    </div>
</div>
    @error('nilai_produksi')
    <span class="text-xs text-red-
400">{{ $message }}</span>
    @enderror
</div>
<div class="sm:col-span-3">
    <label class="block text-sm
font-medium text-gray-700"
for="bentuk_badan_usaha">
        Bentuk Badan Usaha
    </label>
    <div class="mt-1">
        <input
            class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
            id="bentuk_badan_usaha"
name="bentuk_badan_usaha" type="text"
            value="{{
old('bentuk_badan_usaha', $business-
>bentuk_badan_usaha) }}">
        </div>
        @error('bentuk_badan_usaha')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-3">
        <label class="block text-sm
font-medium text-gray-700" for="nama_produk">
            Nama Produk
        </label>
        <div class="mt-1">
            <input
                class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                id="nama_produk"
name="nama_produk" type="text"
                value="{{
old('nama_produk', $business->nama_produk) }}"
autocomplete="nama_produk">
            </div>
            @error('nama_produk')
            <span class="text-xs text-red-
400">{{ $message }}</span>
            @enderror
        </div>
        <div class="sm:col-span-3">
            <label class="block text-sm
font-medium text-gray-700" for="bahan_baku">
                Bahan Baku
            </label>
            <div class="mt-1">
                <input
                    class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                    id="bahan_baku"
name="bahan_baku" type="text"
                    value="{{
old('bahan_baku', $business->bahan_baku) }}"
autocomplete="bahan_baku">

```

```

    </div>
    @error('bahan_baku')
    <span class="text-xs text-red-
400">{{ $message }}</span>
    @enderror
</div>
<div class="sm:col-span-6">
    <h4 class="text-lg font-
medium text-gray-800">Data Lokasi</h4>
</div>
<div class="sm:col-span-3">
    <label class="block text-sm
font-medium text-gray-700" for="nilai_produksi">
        Titik Latitude
    </label>
    <div class="mt-1">
        <input
            class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
            id="lat" name="lat"
type="text"
            value="{{ old('lat',
$bussiness->lat) }}" readonly>
        </div>
        @error('lat')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-3">
        <label class="block text-sm
font-medium text-gray-700" for="nilai_produksi">
            Titik Longitude
        </label>
        <div class="mt-1">
            <input
                class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                id="lng" name="lng"
type="text"
                value="{{ old('lng',
$bussiness->lng) }}" readonly>
        </div>
        @error('lng')
        <span class="text-xs text-red-
400">{{ $message }}</span>
        @enderror
    </div>
    <div class="sm:col-span-6">
        <label class="block text-sm
font-medium text-gray-700" for="lokasi">
            Lokasi
        </label>
        <div class="mt-1">
            <input
                class="block w-full
rounded-md border-gray-300 shadow-sm focus:border-
indigo-500 focus:ring-indigo-500 sm:text-sm"
                id="lokasi"
name="lokasi" type="text"
                value="{{ old('lokasi',
$bussiness->lokasi) }}" autocomplete="lokasi"
readonly>
        </div>
        @error('lokasi')
        <span class="text-xs text-red-
400">{{ $message }}</span>

```



```

<th scope="col"
class="relative px-6 py-3">
    <span class="sr-
only">Edit</span>
    </th>
</tr>
</thead>
<tbody>
    @foreach ($bussinesses as
$bussiness)
        <tr class="odd:bg-white even:bg-
gray-50">
            <td class="px-6 py-4 text-sm
font-medium text-gray-900 whitespace-nowrap">{{
                $bussiness->nama_pemilik
            }}
            </td>
            <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
                $bussiness->nama_usaha
            }}</td>
            <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
                $bussiness->alamat_pemilik
            }}</td>
            <td class="px-6 py-4 text-sm
text-gray-500 whitespace-nowrap">{{
                $bussiness->no_hp_pemilik
            }}</td>
            <td
                class="flex px-6 py-4 space-
x-1 text-sm font-medium text-right max-w-1
whitespace-nowrap">
                <a href="{{ {
                    route('industri.edit', $bussiness) }}"
                    class="text-indigo-600
                    hover:text-indigo-900">Edit</a>
                <form method="POST"
                    action="{{ { route('industri.destroy', $bussiness) }}">
                    @csrf
                    @method('DELETE')
                    <button type="submit"
                        class="text-red-600
                        hover:text-red-900">Delete</button>
                    </form>
                </td>
            </tr>
        @endforeach
    </tbody>
</table>
</div>
</div>
</div>
</div>
</div>
</div>
</x-app-layout>

text/x-generic edit.blade.php ( ASCII text )
<x-app-layout>
    <x-slot name="header">
        <h2 class="text-xl font-semibold leading-tight
text-gray-800">
            Sabtu
        </h2>
    </x-slot>

    <div class="py-12">

```

```
<div class="mx-auto max-w-7xl sm:px-6 lg:px-8">
    <div class="flex flex-col">
        <div class="-my-2 overflow-x-auto sm:mx-6 lg:mx-8">
            <div class="inline-block min-w-full py-2 align-middle sm:px-6 lg:px-8">
                <div class="p-8 overflow-hidden bg-white border-b border-gray-200 shadow sm:rounded-lg">
                    <form class="space-y-8 divide-y divide-gray-200" method="POST" action="{{ route('satuan.update', $unit) }}">
                        <div class="grid grid-cols-1 mt-6 gap-y-6 gap-x-4 sm:grid-cols-6">
                            @csrf
                            @method('PUT')
                            <div class="sm:col-span-3">
                                <label for="satuan">
                                    class="block text-sm font-medium text-gray-700">Satuan
                                </label>
                                <div class="mt-1">
                                    <input type="text" name="name" id="name" autocomplete="name" class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm" value="{{ old('name', $unit->name) }}">
                                </div>
                                @error('name')
                                <span class="text-xs text-red-400">{{ $message }}</span>
                                @enderror
                            </div>
                            <div class="p-5 text-right bg-gray-200 rounded-md">
                                <button type="submit" class="inline-flex items-center px-4 py-2 ml-3 text-sm font-medium text-white bg-indigo-600 border border-transparent rounded-md shadow-sm hover:bg-indigo-700 focus:outline-none focus:ring-2 focus:ring-offset-2 focus:ring-indigo-500">
                                    Simpan
                                </button>
                            </div>
                        </form>
                    </div>
                </div>
            </div>
        </div>
    </div>
</x-app-layout>

text/x-generic index.blade.php ( HTML document, ASCII text )
<x-app-layout>
    <x-slot name="header">
        <div class="flex justify-between w-full">
            <h2 class="text-xl font-semibold leading-tight text-gray-800">
                Satuan
            </h2>
```

```

<div class="flex mt-4 md:mt-0 md:ml-4">
  <a href="{{ route('satuan.create') }}"
    class="inline-flex items-center px-4 py-2
ml-3 text-sm font-medium text-white bg-indigo-600
border border-transparent rounded-md shadow-sm
hover:bg-indigo-700 focus:outline-none focus:ring-2
focus:ring-offset-2 focus:ring-indigo-
500">Tambah</a>
</div>
</div>
</x-slot>

<div class="py-12">
  <div class="mx-auto max-w-7xl sm:px-6 lg:px-
8">
    <div class="flex flex-col">
      <div class="-my-2 overflow-x-auto sm:-mx-6
lg:-mx-8">
        <div class="inline-block min-w-full py-2
align-middle sm:px-6 lg:px-8">
          <div class="overflow-hidden border-b
border-gray-200 shadow sm:rounded-lg">
            <table class="min-w-full divide-y
divide-gray-200">
              <thead class="bg-gray-50">
                <tr>
                  <th scope="col"
                    class="px-6 py-3 text-xs
font-medium tracking-wider text-left text-gray-500
uppercase">
                    Satuan</th>
                  <th scope="col"
                    class="relative px-6 py-3">
                    <span class="sr-
only">Edit</span>
                  </th>
                </tr>
              </thead>
              <tbody>
                @foreach ($units as $unit)
                  <tr class="odd:bg-white even:bg-
gray-50">
                    <td class="px-6 py-4 text-sm
font-medium text-gray-900 whitespace-nowrap">{{
$unit->name }}
                    </td>
                    <td
                      class="flex px-6 py-4 space-
x-1 text-sm font-medium text-right max-w-0
whitespace-nowrap">
                      <a href="{{
route('satuan.edit', $unit) }}"
                        class="text-indigo-600
hover:text-indigo-900">Edit</a>
                      <form method="POST"
action="{{ route('satuan.destroy', $unit) }}">
                        @csrf
                        @method('DELETE')
                        <button type="submit"
                          class="text-red-600
hover:text-red-900">Delete</button>
                      </form>
                    </td>
                  </tr>
                @endforeach
              </tbody>
            </table>
          </div>
        </div>
      </div>
    </div>
  </div>

```

```

</div>
</div>
</div>
</x-app-layout>

text/x-generic create.blade.php ( ASCII text )
<x-app-layout>
  <x-slot name="header">
    <h2 class="text-xl font-semibold leading-tight
text-gray-800">
      Satuan
    </h2>
  </x-slot>

  <div class="py-12">
    <div class="mx-auto max-w-7xl sm:px-6 lg:px-
8">
      <div class="flex flex-col">
        <div class="-my-2 overflow-x-auto sm:-mx-6
lg:-mx-8">
          <div class="inline-block min-w-full py-2
align-middle sm:px-6 lg:px-8">
            <div class="p-8 overflow-hidden bg-
white border-b border-gray-200 shadow sm:rounded-
lg">
              <form class="space-y-8 divide-y
divide-gray-200" method="POST"
                action="{{ route('satuan.store')
}}">
                <div class="grid grid-cols-1 mt-6
gap-y-6 gap-x-4 sm:grid-cols-6">
                  @csrf
                  <div class="sm:col-span-3">
                    <label for="satuan"
class="block text-sm font-medium text-gray-700">
                      Satuan
                    </label>
                    <div class="mt-1">
                      <input type="text"
name="name" id="name" autocomplete="name"
                      class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
                      value="{{ old('name')
}}">
                    </div>
                    @error('name')
                      <span class="text-xs text-red-
400">{{ $message }}</span>
                    @enderror
                  </div>
                  <div class="p-5 text-right bg-gray-
200 rounded-md">
                    <button type="submit"
                      class="inline-flex items-center
px-4 py-2 ml-3 text-sm font-medium text-white bg-
indigo-600 border border-transparent rounded-md
shadow-sm hover:bg-indigo-700 focus:outline-none
focus:ring-2 focus:ring-offset-2 focus:ring-indigo-
500">
                      Simpan
                    </button>
                  </div>
                </form>
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  </div>

```

```

        </div>
    </div>
</div>
</x-app-layout>

text/x-generic index.blade.php ( HTML document,
ASCII text )
<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-
width, initial-scale=1.0">
    <meta http-equiv="X-UA-Compatible"
content="ie=edge">
    <title>Home - Pelaporan UMKM</title>

    <style>
        body {
            background-image:
url('../images/background.jpg');
            background-size: contain;
        }
    </style>
    <!-- Scripts -->
    @vite(['resources/css/app.css', 'resources/js/app.js'])
</head>

<body>
    <div class="relative overflow-hidden">
        <div class="hidden sm:block sm:absolute
sm:inset-y-0 sm:h-full sm:w-full" aria-hidden="true">
            <div class="relative h-full mx-auto max-w-
7xl">
                <svg class="absolute transform right-full
translate-y-1/4 translate-x-1/4 lg:translate-x-1/2"
width="404" height="784" fill="none"
viewBox="0 0 404 784">
                    <defs>
                        <pattern id="f210dbf6-a58d-4871-961e-
36d5016a0f49" x="0" y="0" width="20" height="20"
patternUnits="userSpaceOnUse">
                            <rect x="0" y="0" width="4"
height="4" class="text-gray-200" fill="currentColor" />
                        </pattern>
                    </defs>
                    <rect width="404" height="784"
fill="url(#f210dbf6-a58d-4871-961e-36d5016a0f49)"
/>
                </svg>
                <svg class="absolute transform left-full -
translate-y-3/4 -translate-x-1/4 md:-translate-y-1/2 lg:-
translate-x-1/2"
width="404" height="784" fill="none"
viewBox="0 0 404 784">
                    <defs>
                        <pattern id="5d0dd344-b041-4d26-
bec4-8d33ea57ec9b" x="0" y="0" width="20"
height="20"
                        patternUnits="userSpaceOnUse">
                            <rect x="0" y="0" width="4"
height="4" class="text-gray-200" fill="currentColor" />
                        </pattern>
                    </defs>
                    <rect width="404" height="784"
fill="url(#5d0dd344-b041-4d26-bec4-8d33ea57ec9b)"
/>
                </svg>
            </div>
        </div>
    </div>

```

```

        </div>
    </div>

    <div x-data="{ show: false}" class="relative pt-6
pb-16 sm:pb-24">
        <div>
            <div class="px-4 mx-auto max-w-7xl sm:px-
6">
                <nav class="relative flex items-center
justify-between sm:h-10 md:justify-center"
aria-label="Global">
                    <div class="flex items-center flex-1
md:absolute md:inset-y-0 md:left-0">
                        <div class="flex items-center justify-
between w-full md:w-auto">
                            <a href="/">
                                <span class="sr-
only">Workflow</span>
                            
                        </a>
                    <div class="flex items-center -mr-2
md:hidden">
                        <button type="button"
@click="show = true"
class="inline-flex items-center
justify-center p-2 text-gray-400 rounded-md bg-gray-50
hover:text-gray-500 hover:bg-gray-100 focus:outline-
none focus:ring-2 focus:ring-inset focus:ring-indigo-
500"
aria-expanded="false">
                            <span class="sr-only">Open
main menu</span>
                        <!-- Heroicon name:
outline/menu -->
                            <svg class="w-6 h-6"
xmlns="http://www.w3.org/2000/svg" fill="none"
viewBox="0 0 24 24"
stroke="currentColor" aria-hidden="true">
                                <path stroke-
linecap="round" stroke-linejoin="round" stroke-
width="2"
                                d="M4 6h16M4
12h16M4 18h16" />
                            </svg>
                        </button>
                    </div>
                </div>
            </div>
            <div class="hidden md:absolute md:flex
md:items-center md:justify-end md:inset-y-0 md:right-
0">
                <span class="inline-flex rounded-md
shadow">
                    <a href="{ { route('login') }}"
class="inline-flex items-center
px-4 py-2 text-base font-medium text-indigo-600 bg-
white border border-transparent rounded-md hover:bg-
gray-50">
                        Log in </a>
                </span>
            </div>
        </div>
    </div>
    <!--

```

Mobile menu, show/hide based on menu open state.

```

    Entering: "duration-150 ease-out"
    From: "opacity-0 scale-95"
    To: "opacity-100 scale-100"
    Leaving: "duration-100 ease-in"
    From: "opacity-100 scale-100"
    To: "opacity-0 scale-95"
  -->
  <div x-show="show"
    class="absolute inset-x-0 top-0 z-10 p-2
    transition origin-top-right transform md:hidden">
    <div class="overflow-hidden bg-white
    rounded-lg shadow-md ring-1 ring-black ring-opacity-
    5">
      <div class="flex items-center justify-
    between px-5 pt-4">
        <div>
          
        </div>
        <div class="-mr-2">
          <button type="button"
@click="show = false"
      class="inline-flex items-center
    justify-center p-2 text-gray-400 bg-white rounded-md
    hover:text-gray-500 hover:bg-gray-100 focus:outline-
    none focus:ring-2 focus:ring-inset focus:ring-indigo-
    500">
        <span class="sr-only">Close
    menu</span>
        <!-- Heroicon name: outline/x -->
        <svg class="w-6 h-6"
    xmlns="http://www.w3.org/2000/svg" fill="none"
    viewBox="0 0 24 24"
    stroke="currentColor" aria-hidden="true">
          <path stroke-linecap="round"
    stroke-linejoin="round" stroke-width="2"
    d="M6 18L18 6M6 6L12 12"
    />
        </svg>
      </button>
    </div>
  </div>
  <a href="{{ route('login') }}"
    class="block w-full px-5 py-3 font-
    medium text-center text-indigo-600 bg-gray-50
    hover:bg-gray-100">
    Log in </a>
  </div>
</div>
</div>

<main class="px-4 mx-auto mt-16 max-w-7xl
sm:mt-24">
  <div class="text-center">
    <h1 class="text-4xl font-extrabold
    tracking-tight text-gray-900 mb-28 sm:text-5xl md:text-
    6xl">
      <span class="block xl:inline">Halaman
    pelaporan</span>
      <span class="block text-indigo-600
    xl:inline">UMKM</span>
    </h1>
    {{ -- <div class="max-w-md mx-auto mt-5
    sm:flex sm:justify-center md:mt-8">

```

```

    <div class="rounded-md shadow">
      <a href="{{ route('lapor.create') }}"
        class="flex items-center justify-
    center w-full px-8 py-3 text-base font-medium text-
    white bg-indigo-600 border border-transparent rounded-
    md hover:bg-indigo-700 md:py-4 md:text-lg md:px-
    10">
        Lapor Sekarang </a>
    </div>
  </div> --}}
</div>
</main>
</div>

<div class="py-12">
  <div class="mx-auto max-w-7xl sm:px-6 lg:px-
    8">
    <div class="flex flex-col">
      <div class="-my-2 overflow-x-auto sm:-mx-6
    lg:-mx-8">
        <div class="inline-block min-w-full py-2
    align-middle sm:px-6 lg:px-8">
          <div class="overflow-hidden border-b
    border-gray-200 shadow sm:rounded-lg">
            <table class="min-w-full divide-y
    divide-gray-200">
              <thead class="bg-gray-50">
                <tr>
                  <th scope="col"
                    class="px-6 py-3 text-xs
    font-medium tracking-wider text-left text-gray-500
    uppercase">
                    Nama Pemilik</th>
                  <th scope="col"
                    class="px-6 py-3 text-xs
    font-medium tracking-wider text-left text-gray-500
    uppercase">
                    Nama Usaha</th>
                  <th scope="col"
                    class="px-6 py-3 text-xs
    font-medium tracking-wider text-left text-gray-500
    uppercase">
                    Alamat Pemilik</th>
                  <th scope="col"
                    class="px-6 py-3 text-xs
    font-medium tracking-wider text-left text-gray-500
    uppercase">
                    No HP</th>
                </tr>
              </thead>
              <tbody>
                @foreach ($bussinneses as
    $bussinnes)
                  <tr class="odd:bg-white even:bg-
    gray-50">
                    <td class="px-6 py-4 text-sm
    font-medium text-gray-900 whitespace-nowrap"><a
    class="text-blue-700 hover:underline" href="{{
    route('detail-laporan', $bussinnes) }}">{{
    $bussinnes->nama_pemilik
    }}
                    </a></td>
                    <td class="px-6 py-4 text-sm
    text-gray-500 whitespace-nowrap">{{
    $bussinnes->nama_usaha
    }}</td>
                    <td class="px-6 py-4 text-sm
    text-gray-500 whitespace-nowrap">{{

```

[illegible]

```

    <p>: {{ $bussiness->nama_usaha
  }}</p>
    </div>
  </div>
  <div class="grid grid-cols-3 gap-4">
    <div>
      <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Nama
        Pemilik</label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness-
>nama_pemilik }}</p>
      </div>
    </div>
    <div class="grid grid-cols-3 gap-4">
      <div>
        <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Jenis Kelamin </label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness-
>jenis_kelamin }}</p>
      </div>
    </div>
    <div class="grid grid-cols-3 gap-4">
      <div>
        <label for="alamat_pemilik"
class="block text-sm font-medium text-gray-700">
Alamat Pemilik</label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness-
>alamat_pemilik }}</p>
      </div>
    </div>
    <div class="grid grid-cols-3 gap-4">
      <div>
        <label for="no_hp_pemilik"
class="block text-sm font-medium text-gray-700">
HP</label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness-
>no_hp_pemilik }}</p>
      </div>
    </div>
    <div class="grid grid-cols-3 gap-4">
      <div>
        <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Kecamatan</label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness->kecamatan
  }}</p>
      </div>
    </div>
    <div class="grid grid-cols-3 gap-4">
      <div>
        <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Kelurahan</label>
      </div>
      <div class="col-span-2">
        <p>: {{ $bussiness->kelurahan
  }}</p>
      </div>
    </div>
  </div>

```

```

        </div>
      </div>
      <div class="grid grid-cols-3 gap-4">
        <div>
          <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Nama Produk </label>
        </div>
        <div class="col-span-2">
          <p>: {{ $business-
>nama_produk }}</p>
        </div>
        </div>
        <div class="grid grid-cols-3 gap-4">
          <div>
            <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Tahun Izin</label>
          </div>
          <div class="col-span-2">
            <p>: {{ $business->tahun_izin
}}</p>
          </div>
          </div>
          <div class="grid grid-cols-3 gap-4">
            <div>
              <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700"> No
KBLI</label>
            </div>
            <div class="col-span-2">
              <p>: {{ $business->kbli->kode
}}</p>
            </div>
            </div>
            <div class="grid grid-cols-3 gap-4">
              <div>
                <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Tenaga
                Kerja Laki-laki</label>
              </div>
              <div class="col-span-2">
                <p>: {{ $business->tenaga_laki
}} Orang</p>
              </div>
              </div>
              <div class="grid grid-cols-3 gap-4">
                <div>
                  <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Tenaga Kerja
                  Perempuan</label>
                </div>
                <div class="col-span-2">
                  <p>: {{ $business-
>tenaga_perempuan }} Orang</p>
                </div>
                </div>
                <div class="grid grid-cols-3 gap-4">
                  <div>
                    <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Kapasitas Produksi
                    Perhari</label>
                  </div>
                  <div class="col-span-2">

```

```

          <p>: {{ $business-
>kapasitas_produksi }} {{ $business->unit->name
}}</p>
        </div>
        </div>
        <div class="grid grid-cols-3 gap-4">
          <div>
            <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Nilai Investasi</label>
          </div>
          <div class="col-span-2">
            <p>: Rp. {{
number_format(round($business->nilai_investasi), 0,
',', '.') }}</p>
          </div>
          </div>
          <div class="grid grid-cols-3 gap-4">
            <div>
              <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Nilai Produksi</label>
            </div>
            <div class="col-span-2">
              <p>: Rp. {{
number_format(round($business->nilai_produksi), 0,
',', '.') }}</p>
            </div>
            </div>
            <div class="grid grid-cols-3 gap-4">
              <div>
                <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Bahan Baku </label>
              </div>
              <div class="col-span-2">
                <p>: {{ $business->bahan_baku
}}</p>
              </div>
              </div>
              <div class="grid grid-cols-3 gap-4">
                <div>
                  <label for="nama_pemilik"
class="block text-sm font-medium text-gray-700">
Lokasi </label>
                </div>
                <div class="col-span-2">
                  <p>: {{ $business->lokasi }}
</p>
                </div>
                </div>
                <div>
                  <div>
                    <iframe class="sm:col-span-6"
width="100%" height="450" frameborder="0"
style="border:0" referrerpolicy="no-referrer-when-
downgrade"
src="https://www.google.com/maps/embed/v1/place?ke
y=AlzaSyBdi77wWAhcBbH4ISp36MM3RO5V7AcuC
w4&q={{ $business->lat }},{ $business->lng
}}&center={{ $business->lat }},{ $business->lng
}}&zoom=15" allowfullscreen>
                    </iframe>
                    <a href="{{ route('home') }}"
class="inline-flex items-center px-4
py-2 ml-3 text-sm font-medium text-white bg-indigo-
600 border border-transparent rounded-md shadow-sm
hover:bg-indigo-700 focus:outline-none focus:ring-2
focus:ring-offset-2 focus:ring-indigo-500">
Kembali

```



```

class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('kecamatan') }}">
</div>
@error('id_kecamatan')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="id_kelurahan"
class="block text-sm font-medium text-gray-700">
Kelurahan </label>
<div class="mt-1">
<input type="text"
name="kelurahan" id="kelurahan"
autocomplete="kelurahan"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('kelurahan') }}">
</div>
@error('id_kelurahan')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="id_kbli"
class="block text-sm font-medium text-gray-700">
Bentuk Usaha </label>
<div class="mt-1">
<select name="id_kbli"
id="id_kbli" autocomplete="id_kbli"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
@change="kbliChange"
x-model="selectedId">
<template x-for="kbli in
list_kbli" :key="kbli.id">
<option
:value="kbli.id" x-text="kbli.name">
</option>
</template>
</select>
</div>
@error('id_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="tahun_izin"
class="block text-sm font-medium text-gray-700">
Tahun
Izin </label>
<div class="mt-1">
<input type="text"
name="tahun_izin" id="tahun_izin"
autocomplete="tahun_izin"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"

```

```

value="{{
old('tahun_izin') }}">
</div>
@error('tahun_izin')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="no_kbli"
class="block text-sm font-medium text-gray-700"> No
KBLI
</label>
<div class="mt-1">
<input type="text" readonly
name="no_kbli" id="no_kbli"
autocomplete="no_kbli"
class="block w-full bg-
gray-200 border-gray-300 rounded-md shadow-sm
focus:ring-indigo-500 focus:border-indigo-500 sm:text-
sm"
:value="getSelectedText()">
</div>
@error('no_kbli')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label for="tenaga_laki"
class="block text-sm font-medium text-gray-700">
Tenaga
Kerja Laki-laki
</label>
<div class="mt-1">
<input type="text"
name="tenaga_laki" id="tenaga_laki"
autocomplete="tenaga_laki"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('tenaga_laki') }}">
</div>
@error('tenaga_laki')
<span class="text-xs text-red-
400">{{ $message }}</span>
@enderror
</div>
<div class="sm:col-span-3">
<label
for="tenaga_perempuan" class="block text-sm font-
medium text-gray-700">
Tenaga Kerja
Perempuan
</label>
<div class="mt-1">
<input type="text"
name="tenaga_perempuan" id="tenaga_perempuan"
autocomplete="tenaga_perempuan"
class="block w-full
border-gray-300 rounded-md shadow-sm focus:ring-
indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{
old('tenaga_perempuan') }}">
</div>

```



```

        @error('tenaga_perempuan')
        <span class="text-xs text-red-400">{{ $message }}</span>
    @enderror
</div>
<div class="sm:col-span-3">
    <label
for="kapasitas_produksi" class="block text-sm font-medium text-gray-700">
        Kapasitas Produksi Perhari
    </label>
    <div class="mt-1">
        <input type="text"
name="kapasitas_produksi" id="kapasitas_produksi"
autocomplete="kapasitas_produksi"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{ {
old('kapasitas_produksi') }}">
    </div>
    @error('kapasitas_produksi')
    <span class="text-xs text-red-400">{{ $message }}</span>
    @enderror
</div>
<div class="sm:col-span-3">
    <label for="satuan"
class="block text-sm font-medium text-gray-700">
Satuan
    </label>
    <div class="mt-1">
        <select name="id_satuan"
id="id_satuan"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm">
            @foreach ($units as $unit)
                <option value="{{ $unit->id }}" {{ old("id_satuan")==$unit->id ? 'selected' : "" }}>{{ $unit->name }}
            </option>
            @endforeach
        </select>
    </div>
    @error('id_satuan')
    <span class="text-xs text-red-400">{{ $message }}</span>
    @enderror
</div>
<div class="sm:col-span-3">
    <label for="nilai_investasi"
class="block text-sm font-medium text-gray-700">
        Nilai Investasi
    </label>
    <div class="mt-1">
        <input type="text"
name="nilai_investasi" id="nilai_investasi"
autocomplete="nilai_investasi"
class="block w-full border-gray-300 rounded-md shadow-sm focus:ring-indigo-500 focus:border-indigo-500 sm:text-sm"
value="{{ {
old('nilai_investasi') }}">

```

[illegible]

```
        return selectedKbli.length > 0 ?  
selectedKbli[0].kode : "";  
    },  
    init() {
```

```
        this.selectedId = this.list_kbli[0].id ?? null;  
    }  
});
```

Lampiran 2 – Kartu Monitoring Seminar Proposal



KARTU MONITORING BIMBINGAN
 MAHASISWA PROGRAM STUDI TEKNIK INFORMATIKA
 FAKULTAS TEKNIK
 UNIVERSITAS MUHAMMADIYAH PAREPARE

PROPOSAL

| | |
|---|---|
| Mahasiswa : Mardiansyah | Pembimbing I : Muhammad Basri, S.T, MT. |
| NIM : 218280122 | Pembimbing II : Wahyuddin, S.kom., M.kom. |
| Judul Skripsi : PERANCANGAN SISTEM INFORMASI PADA BIDANG PERINDUSTRIAN DINAS PERDAGANGAN KOTA PAREPARE | |

| ARAHAN PEMBIMBING I | HARI/TGL & PARAF PEMBIMBING | ARAHAN PEMBIMBING II | HARI/TGL & PARAF PEMBIMBING |
|---------------------|-----------------------------|---|-----------------------------|
| Konsultasi 1 | | Konsultasi 1
- Tambahkan teori pada BAB II | 5/8/22
/k |
| Konsultasi 2 | | Konsultasi 2
- perbaiki desain sistem | 6/8/22
/k |
| Konsultasi 3 | | Konsultasi 3
perjelas Apa yg mau di bikin | /k |
| Konsultasi 4 | | Konsultasi 4 | |
| Konsultasi 5 | | Konsultasi 5 | |

Lanjut ke halaman sebelah...

Perhatian :

1. Mahasiswa wajib konsultasi minimal 5 kali
2. Kartu ini wajib dibawa oleh mahasiswa setiap konsultasi dan diisi oleh Pembimbing
3. Kartu ini wajib dilampirkan pada laporan skripsi dan menjadi salah satu persyaratan untuk ikut seminar proposal/ujian skripsi
4. Kartu ini dicetak di atas kertas karton berwarna hijau muda dan dicetak timbal balik



Lampiran 3 – Kartu Monitoring Seminar Hasil



KARTU MONITORING BIMBINGAN
 MAHASISWA PROGRAM STUDI TEKNIK INFORMATIKA
 FAKULTAS TEKNIK
 UNIVERSITAS MUHAMMADIYAH PAREPARE

HASIL

| | |
|--|--|
| MAHASISWA : MARDIANSYAH | Pembimbing I : Muh. Basri, S.T.,M.T |
| NIM : 218 280 122 | Pembimbing II : Wahyuddin, S.Kom., M.Kom |
| Judul Skripsi : PERANCANGAN SISTEM INFORMASI PADA BIDANG PERINDUSTRIAN DINAS PERDAGANGAN KOTA PAREPARE | |

| ARAHAN PEMBIMBING I | HARI/TGL & PARAF PEMBIMBING | ARAHAN PEMBIMBING II | HARI/TGL & PARAF PEMBIMBING |
|--|---|---|---|
| Konsultasi 1
Tentukan arah dan
tujuan. |  | Konsultasi 1
Perbaiki data aplikasi |  |
| Konsultasi 2
Kumpulkan data. |  | Konsultasi 2
- ikuti format
penulisan |  |
| Konsultasi 3 | | Konsultasi 3
- lengkapi data
penelitian |  |
| Konsultasi 4 | | Konsultasi 4
Aa |  |
| Konsultasi 5 | | Konsultasi 5 | |

Lanjut ke halaman sebelah...

Perhatian :

1. Mahasiswa wajib konsultasi minimal 5 kali
2. Kartu ini wajib dibawa oleh mahasiswa disetiap konsultasi dan diisi oleh Pembimbing
3. Kartu ini wajib dilampirkan pada laporan skripsi dan menjadi salah satu persyaratan untuk ikut seminar proposal/ujian skripsi
4. Kartu ini dicetak di atas kertas karton berwarna hijau muda dan dicetak timbal balik

Lampiran 4 – Kartu Monitoring Ujian Tutup

Lanjutan...

| ARAHAN PEMBIMBING I | HARI/TGL & PARAF PEMBIMBING | ARAHAN PEMBIMBING II | HARI/TGL & PARAF PEMBIMBING |
|---------------------|-----------------------------|--|-----------------------------|
| Konsultasi 6 | | Konsultasi 6
- Perbaiki ukuran gambar
- daftar isi | |
| Konsultasi 7 | | Konsultasi 7
- white box
- kata asing singkatan | |
| Konsultasi 8 | | Konsultasi 8
- Ikuti Panduan | |
| Konsultasi 9 | | Konsultasi 9 | |
| Konsultasi 10 | | Konsultasi 10 | |

Parepare, 3 Agustus 2023

Mengetahui
Ketua Program Studi

Marlina, S.Kom.,M.Kom.
NBM. 1162 680

Mahasiswa

MARDIANSYAH
NIM. 218280122

Perhatian :

1. Mahasiswa wajib konsultasi minimal 5 kali
2. Kartu ini wajib dibawa oleh mahasiswa disetiap konsultasi dan diisi oleh Pembimbing
3. Kartu ini wajib dilampirkan pada laporan skripsi dan menjadi salah satu persyaratan untuk ikut seminar proposal/ujian skripsi
4. Kartu ini dicetak di atas kertas karton berwarna hijau muda dan dicetak timbal balik

